



Product Information

CT 413

Polyester Silicone Splicing Tape

Description:

1 mil polyester film tape with a 1.5 mil pre-cured silicone adhesive. Electrically and mechanically stable at operating at high temperatures. (Available in different colors)

Application:

- Used for splicing silicone coated papers
- Designed to perform in all phases of the masking of PCB production

Technical Data

<i>Adhesive</i>	Pre-Cured Silicone
<i>Substrate</i>	Polyester Film
<i>Thickness (mils)</i>	2.5 (0.0635 mm)
<i>Adhesion to Steel (oz/in of width)</i>	40 (11 N/25mm)
<i>Tensile Strength (lbs/in of width)</i>	28 (125.3 N/25mm)
<i>Elongation (% at Break)</i>	115
<i>Temperature Resistance</i>	400°F (204°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079

Fax: 828-322-7268

www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.