



## Product Information

**CT 416**

**PCB Masking Tape**

### Description:

1 mil polyester film tape with a red silicone adhesive.

### Application:

- Stop-off applications in the production of printed circuit boards
- Particularly for use in tin/lead stripping
- "Gold finger" plating operations
- Silicone splicing

### Technical Data

<i>Adhesive</i>	Silicone
<i>Substrate</i>	Polyester Film
<i>Thickness (mils)</i>	4 (0.102 mm)
<i>Adhesion to Steel (oz/in of width)</i>	25 (6.8 N/25mm)
<i>Tensile Strength (lbs/in of width)</i>	23 (101 N/25mm)
<i>Elongation (% at Break)</i>	100

*The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.*

Carolina Tape & Supply Corporation  
502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079

Fax: 828-322-7268

[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.