



Product Information

CT 433 Silicone Splicing/Polyester Film Tape

Description:

2 mil, polyester film tape coated with a specially-formulated, high adhesion, non-residue, pure silicone adhesive (translucent red).

Application:

- High performance leader card splicing tape used for bonding of photographic film in automated processing equipment
- Provides excellent holding power
- Great chemical and heat resistance

Technical Data

Adhesive	Silicone
Substrate	PE Film
Thickness (mils)	3.5 (0.089 mm)
Adhesion to Steel (oz/in of width)	35 (9.6 N/25mm)
Tensile Strength (lbs/in of width)	55 (246.1 N/25mm)
Elongation (% at Break)	171
Service Temperature	400°F (204°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.