

## **Product Information**

## CT 500 Performance Grade Tensilized Polypropylene Tape

## **Description:**

Performance grade, tensilized polypropylene backing with a rubber adhesive (available in black, orange, and white).

## **Application:**

- Regular duty TPP strapping tape used in a wide variety of strapping, palletizing, unitizing, reinforcing and bundling
- Out performs typical filament tapes by preventing load shift during transit

Technical Data	
Adhesive	Rubber
Substrate	Polypropylene
Thickness (mils)	2.7 (0.069 mm)
Adhesion to Steel (oz/in of width)	46.6 (5.1 N/cm)
Tensile Strength (lbs/in of width)	94.8 (166 N/cm)
Elongation (% at Break)	35

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079 Fax: 828-322-7268 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.