



## Product Information

**CT 503**

## Medium Strength PET Strapping Tape

### Description:

Medium strength, fiberglass reinforced, polyester strapping tape with a solvent-based rubber adhesive.

### Application:

- General purpose strapping, palletizing and unitizing applications where a medium strength tape is needed

### Technical Data

<i>Adhesive</i>	Solvent-Based Rubber
<i>Substrate</i>	Fiberglass Reinforced PET
<i>Thickness (mils)</i>	5.6 (0.14 mm)
<i>Adhesion to Steel (oz/in of width)</i>	39 (10.7 N/25mm)
<i>Tensile Strength (lbs/in of width)</i>	175 (766 N/25mm)
<i>Elongation (% at Break)</i>	4
<i>Operating Temperature</i>	40°F to 200°F (4°C to 93°C)

*The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.*

Carolina Tape & Supply Corporation  
502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079

Fax: 828-322-7268

[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.