



Product Information

CT 504

High Strength PET Strapping Tape

Description:

High strength, fiberglass reinforced, polyester strapping tape with a solvent-based rubber adhesive used for more demanding applications.

Application:

- More demanding industrial strapping, palletizing, and unitizing applications where a high performance tape is required

Technical Data

<i>Adhesive</i>	Solvent-Based Rubber
<i>Substrate</i>	Fiberglass Reinforced PET
<i>Thickness (mils)</i>	6.2 (0.15 mm)
<i>Adhesion to Steel (oz/in of width)</i>	40 (11 N/25mm)
<i>Tensile Strength (lbs/in of width)</i>	275 (1204 N/25mm)
<i>Elongation (% at Break)</i>	4
<i>Operating Temperature</i>	40°F to 200°F (4°C to 93°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.