

Product Information

CT 518 Medium Duty Tensilized Polypropylene Filament

_							
n	OC	cri	m	ti	0	m	×
\mathbf{L}	c_{2}		w	u	v	11	

Medium duty, tensilized polypropylene filament tape with a rubber adhesive (yellow).

Application:

• Medium duty bundling, strapping tubing, wire, and core starting

Technical Data						
Adhesive	Rubber					
Substrate	Tensilized Polypropylene					
Thickness (mils)	4.1 (0.104 mm)					
Adhesion to Steel (oz/in of width)	50.2 (13.72 N/25mm)					
Tensile Strength (Ibs/in of width)	142.8 (635.3 N/25mm)					
Elongation (% at Break)	35					

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079 Fax: 828-322-7268 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.