

**Product Information** 

## CT 600 G

## General Purpose Waterproof Duct Tape

## **Description**:

General purpose grade, waterproof, polycoated cloth duct tape with a natural rubber adhesive (silver and other colors available).

## **Application:**

• Carpet, plumbing, HVAC, asbestos removal, waterproof packaging, patching, splicing, bundling, and color coding

• Conformable, tears easily with no twist or curl

Meets Specs: UL 723, Flame Spread Index-5, Smoke Development Index-7

Technical Data	
Adhesive	Natural Rubber
Substrate	Waterproof Polycoated Cloth
Thickness (mils)	9 (0.23 mm)
Adhesion to Steel (oz/in of width)	50 (5.47 N/10mm)
Tensile Strength (Ibs/in of width)	22 (38.5 N/10mm)
Elongation (% at Break)	16
Service Temperature	50°F to 200°F (10°C to 93°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St. Pl. SE, Hickory, NC 28602 Phone: 800-237-6079 Fax: 828-322-7268 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.