



Product Information

CT 604 Premium Grade Waterproof Polycoated Duct Tape

Description:

Premium grade and waterproof polycoated cloth duct tape with a natural rubber adhesive (silver and other colors available).

Application:

- Indoor/outdoor tape used in nuclear power plants applications to seal end caps on stainless steel pipes, hold labels/signs on stainless steel pipes, and seal HVAC metal duct work

Meets Specs: ANSI No. 45.2.2; NRC Guide 1.38.

Technical Data

Adhesive	Natural Rubber
Substrate	Waterproof Polycoated Cloth
Thickness (mils)	13 (0.33 mm)
Adhesion to Steel (oz/in of width)	60 (6.57 N/10mm)
Tensile Strength (lbs/in of width)	36 (63 N/10mm)
Elongation (% at Break)	14
Service Temperature	50°F to 200°F (10°C to 93°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.