



## Product Information

**CT 606**

**Dead Soft Printed Aluminum Foil Tape**

### Description:

2 mil, dead soft printed aluminum foil with an acrylic adhesive.

### Application:

- To make fiberglass duct board joins and seams air tight
- Resists vapors and other contaminants

*Meets Specs: AFTS-100-93; UL 181A-P Listed, Flame Spread Index-25, Smoke Development Index-1*

### Technical Data

<i>Adhesive</i>	Acrylic
<i>Substrate</i>	Dead Soft Aluminum Foil
<i>Thickness (mils)</i>	6.8 (0.17 mm)
<i>Adhesion to Steel (oz/in of width)</i>	70 (7.66 N/10mm)
<i>Tensile Strength (lbs/in of width)</i>	25 (43.8 N/10mm)
<i>Elongation (% at Break)</i>	2
<i>Service Temperature</i>	-20°F to 260°F (-29°C to 127°C)

*The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.*

Carolina Tape & Supply Corporation  
502 19th St. Pl. SE, Hickory, NC 28602  
Phone: 800-237-6079  
Fax: 828-322-7268  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.