



Product Information

CT 607 **General Purpose Dead Soft Printed Aluminum Foil Tape**

Description:

General purpose grade, 2 mil dead soft printed aluminum foil with a clear, aggressive acrylic adhesive and removable liner.

Application:

- Non-critical applications such as sealing out dust and moisture, masking and duct sealing
- Very conformable
- Provides service from 0°F to 150°F

Technical Data

<i>Adhesive</i>	Aggressive Acrylic
<i>Substrate</i>	Dead Soft Aluminum Foil
<i>Thickness (mils)</i>	3.3 (0.084 mm)
<i>Adhesion to Steel (oz/in of width)</i>	90 (9.9 N/cm)
<i>Tensile Strength (lbs/in of width)</i>	17 (30 N/cm)
<i>Elongation (% at Break)</i>	3.5
<i>Service Temperature</i>	0°F to 150°F (-17.8°C to 65.6°C)
<i>Min. Application Temperature</i>	-25°F (-32°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.