



## Product Information

**CT 609**

**All Temperature Laminated FSK**

### Description:

Laminated foil/scrim/kraft tape with a high tack and all weather synthetic rubber adhesive and a paper release line. This tape offers a permanent bond and resists water vapor and smoke transmission.

### Application:

- Sealing, seaming, and joining scrim-reinforced pipe and duct insulation in all weather conditions
- Resists water vapor and smoke transmissions

*Meets Spec: UL 723; Flame Spread Index-10, Smoke Development Index-10; US Green Building Council - LEED® Point contributor product.*

### Technical Data

<i>Adhesive</i>	All Weather Synthetic Rubber
<i>Substrate</i>	Laminated FSK
<i>Total Thickness (mils)</i>	9.4 (0.24 mm)
<i>Adhesion to Steel (oz/in of width)</i>	60 (6.57 N/10mm)
<i>Tensile Strength (lbs/in of width)</i>	40 (70.1 N/10mm)
<i>Elongation (% at Break)</i>	1
<i>Application Temperature</i>	32°F to 230°F (0°C to 110°C)

*The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.*

Carolina Tape & Supply Corporation  
502 19th St. Pl. SE, Hickory, NC 28602  
Phone: 800-237-6079  
Fax: 828-322-7268  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.