



## Product Information

**CT 612**

### Insulated All Surface Jacket Tape

#### Description:

Insulated, HVA all surface jacket with an all temperature acrylic adhesive and UL listed backing.

#### Application:

- Butt joint cold and dual temp duct and pipe systems
- Seal seams and pipe coverings

*Meets Spec: UL listed*

#### Technical Data

<i>Adhesive</i>	Acrylic, All Temperature
<i>Substrate</i>	All Surface Jacket
<i>Total Thickness (mils)</i>	12.6 (0.32 mm)
<i>Adhesion to Steel (oz/in of width)</i>	80 (8.76 N/10mm)
<i>Tensile Strength (lbs/in of width)</i>	50 (87.6 N/10mm)
<i>Elongation (% at Break)</i>	6.7
<i>Service Temperature</i>	-20°F to 260°F( -29°C to 127°C)

*The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.*

Carolina Tape & Supply Corporation  
502 19th St. Pl. SE, Hickory, NC 28602  
Phone: 800-237-6079  
Fax: 828-322-7268  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.