

## **Product Information**

**CT 613** 

## **Embossed White Vinyl Seaming Tape**

## **Description:**

Embossed white vinyl tape with an acrylic adhesive

## **Application:**

• Repair and seam metal building insulation and hot water heater kits

Meets Spec: UL Classified

Technical Data	
Adhesive	Acrylic
Substrate	Embossed Vinyl
Total Thickness (mils)	4.6 (0.12 mm)
Adhesion to Steel (oz/in of width)	35 (9.8 N/25mm)
Tensile Strength (lbs/in of width)	7 (31.6 N/25mm)
Elongation (% at Break)	100
Service Temperature	-40°F to 225°F( -40°C to 107°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St. Pl. SE, Hickory, NC 28602

Phone: 800-237-6079 Fax: 828-322-7268 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.