

Product Information

CT 621 Waterproof Polycoated Cloth Duct Tape

Description:

Versatile grade, waterproof polycoated cloth duct tape with a high tack natural rubber adhesive.

Application:

• Economical, superior performance, super wet stick and holding power for use in HVAC, asbestos removal, industrial packaging, bundling, and as bottom board tape in manufactured homes

Meets Spec: UL 723, Flame Spread Index-10, Smoke Development Index-10; HUD Std. 280-715C.

Technical Data	
Adhesive	Natural Rubber
Substrate	Waterproof Polycoated Cloth
Total Thickness (mils)	10 (0.25mm)
Adhesion to Steel (oz/in of width)	71 (7.77 N/10mm)
Tensile Strength (Ibs/in of width)	22 (38.5 N/10mm)
Elongation (% at Break)	16
Service Temperature	25°F to 200°F (-4°C to 93°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St. Pl. SE, Hickory, NC 28602 Phone: 800-237-6079 Fax: 828-322-7268 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.