



Product Information

CT 637

Aluminum Foil Vent Tape

Description:

Aluminum foil/non-woven vent tape (uses #647 stock) with a high tack adhesive.

Application:

- Vent tape
- Uses #607 stock for anti-dust venting, outgassing and airflow sealer

Meets Spec: UL 723, Flame Spread Index-10, Smoke Development Index-10; HUD Std. 280-715C.

Technical Data

Adhesive	High Tack Acrylic
Substrate	Aluminum Foil/Non-Woven
Total Thickness (mils)	3.3 (0.084 mm)
Adhesion to Steel (oz/in of width)	90 (9.9 N/cm)
Tensile Strength (lbs/in of width)	17 (30 N/cm)
Elongation (% at Break)	3.5
Service Temperature	0°F to 150°F (-17.8°C to 65.6°C)
Application Temperature (min)	-25°F (-32°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.