



Product Information

CT 657

Premium Printed Polycoated Cloth Duct Tape

Description:

Premium grade, printed polycoated cloth duct tape with a UL 181B-FX adhesive system.

Application:

- HVAC flex duct applications, installing air ducts, air connectors
- Making connections and splices
- Resists flame spread, smoke generation, mold growth, humidity and high temperatures

Meets Spec: UL 723; UL 181B-FX, Flame Spread Index-15, Smoke Development Index-30.

Technical Data

<i>Adhesive</i>	UL 181B-FX Adhesive System
<i>Substrate</i>	Waterproof Polycoated Cloth
<i>Total Thickness (mils)</i>	14 (0.36 mm)
<i>Adhesion to Steel (oz/in of width)</i>	70 (7.66 N/10mm)
<i>Tensile Strength (lbs/in of width)</i>	27 (47.3 N/10mm)
<i>Elongation (% at Break)</i>	10
<i>Service Temperature</i>	50°F to 212°F (10°C to 100°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.