



Product Information

CT #704

Clear Low Density Polyethylene Film Tape

704 is a clear, low density polyethylene film with a rubber adhesive.

Application:

- LDPE splicing and patching low density polyethylene film
- Temporary hold down
- Conformable

TECHNICAL DATA

Adhesive	Rubber
Substrate	Clear Low Density Polyethylene Film
Thickness	5.5 Mils (0.14 mm)
Adhesion to Steel	25 oz/in (2.74 N/cm)
Tensile Strength	11 lbs/in (19.26 N/cm)
Elongation (% at Break)	400
Operating Temperature	-40°F to 190°F (10°C to 88°C)
Application Temperature	50°F to 120°F (10°C to 49°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.