



Product Information

CT #710

Production Grade BOPP Film

710 is a production grade, 30 µm cast BOPP film with an aggressive synthetic rubber/resin hot melt adhesive.

Meets Specs: CID-A-A-1684C; ASTM-D1974.

Application:

- General purpose packaging, holding, and repairing of manual or automated sealing of medium weight cartons in normal packaging and shipping environments

TECHNICAL DATA

Adhesive	Synthetic Rubber/Resin Hot Melt
Substrate	30 µm Cast BOPP Film
Thickness	1.9 Mils (0.05 mm)
Adhesion to Steel	44 oz/in (4.82 N/10mm)
Tensile Strength	44 lbs/in (77.1 N/10mm)
Elongation (% at Break)	150
Service Temperature	-20°F to 150°F (-29°C to 66°C)
Application Temperature	35°F to 110°F (2°C to 43°C)
Holding Power to Fiberboard	15,000+ minutes

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.