



Product Information

CT #711

Performance Grade BOPP Film

711 is a performance grade, 35 µm cast biaxially-oriented polypropylene film with an aggressive synthetic rubber/resin hot melt adhesive.

Meets Specs: CID-A-A-1684C; ASTM-D1974; ASTM D-5486M, Type V.

Application:

- Ideal for automated sealing of medium weight cartons subjected to additional handling stress
- Excellent quick stick and holding power to fiberboard

TECHNICAL DATA

Adhesive	Aggressive Rubber/Resin Hot Melt
Substrate	35 µm Cast BOPP Film
Thickness	2.2 Mils (0.06 mm)
Adhesion to Steel	47 oz/in (5.14 N/10mm)
Tensile Strength	30 lbs/in (52.5 N/10mm)
Elongation (% at Break)	150
Service Temperature	-20°F to 150°F (-29°C to 66°C)
Application Temperature	35°F to 110°F (2°C to 43°C)
Holding Power to Fiberboard	20,000+ minutes

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.