



## Product Information

### CT #717

### Premium Grade Hazard Striped Platicized Film

717 is a premium grade, hazard striped plasticized film with a synthetic rubber/resin adhesive. It is available with or without liner and striped colors.

Meets Specs: OSHA Regulations 1910:22 and 1920:144.

#### Application:

- Highly visible hazardous marking tape used to identify/warn of certain existing conditions and areas

#### TECHNICAL DATA

<b>Adhesive</b>	Synthetic Rubber/Resin
<b>Substrate</b>	Hazard Striped Plasticized Film
<b>Thickness</b>	9 Mils (0.225 mm)
<b>Adhesion to Steel</b>	22 oz/in
<b>Tensile Strength</b>	33 lbs/in
<b>Elongation (% at Break)</b>	200
<b>Temperature Resistance</b>	-20°F to 176°F (-28.9°C to 80°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation  
502 19<sup>th</sup> St PL SE, Hickory, NC 28602  
Phone: 800-237-6079  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.