

Product Information

CT #725

Economy Grade Striped Film Tape

725 is an economy grade, stabilized and plasticized shiny SPVC film that is abrasion resistant and has a non-corrosive, natural rubber adhesive (available in different colors).

Meets Specs: A-A-1689B; PPP-T-66E.

Application:

- Warning stripe tape for floor, lane, and aisle marking
- Color coding, identification of safety and caution areas
- Wrapping and insulation of air ducts and underground pipes
- Resists acids, alkalides, oils, moisture, humidity, and corrosion

TECHNICAL DATA

Adhesive	Non- Corrosive Natural Rubber
Substrate	Shiny SPVC Film
Thickness	6.6 Mils (0.17 mm)
Adhesion to Steel	30 oz/in (1.31 N/10mm)
Tensile Strength	15 lbs/in (26.3 N/10mm)
Elongation (% at Break)	200
Service Temp. Min	20°F (-7°C)
Service Temp. Max	140°F (60°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation 502 19th St PL SE, Hickory, NC 28602 Phone: 800-237-6079 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.