



## Product Information

### CT #729

### High Performance Grade Vylon Film Tape

729 is a high performance grade film tape with a 4 mil, clear Vylon film backing and a high grade emulsion acrylic adhesive. This tape offers excellent resistance and a wide operating temperature range.

#### Application:

- Packaging, laminating, edging, hinging, label protection, tabbing, and splicing
- Excellent for separating dissimilar metals to prevent electrolytic corrosion
- Resistance to moisture, aging, weathering, sunlight, chemicals, oils, and acids
- Wide temperature range

#### TECHNICAL DATA

<b>Adhesive</b>	Emulsion Acrylic
-----------------	------------------

<b>Substrate</b>	Clear Vylon Film
------------------	------------------

<b>Thickness</b>	5 Mils
------------------	--------

<b>Adhesion to Steel</b>	35 oz/in
--------------------------	----------

<b>Tensile Strength</b>	180 lbs/in
-------------------------	------------

<b>Elongation</b> (% at Break)	35
-----------------------------------	----

<b>Operating Temperature</b>	-30°F to 200°F (-34°C to 93.3°C)
------------------------------	-------------------------------------

<b>Application Temperature</b>	32°F to 150°F (0°C to 65.6°C)
--------------------------------	----------------------------------

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation  
502 19<sup>th</sup> St PL SE, Hickory, NC 28602  
Phone: 800-237-6079  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.