



Product Information

CT #771

Protective Overlay Polyethylene Film Tape

771 is a black polyethylene film with an acrylic adhesive with high elongation (clear available – 10 case minimum).

Application:

- High elongation tape for protective overlay of surfaces requiring resistance to solvents and chemicals

TECHNICAL DATA

Adhesive	Acrylic
Substrate	Black or Clear Polyethylene Film
Thickness	8 Mils (0.203 mm)
Adhesion to Steel	45 oz/in 4.92 N/cm
Tensile Strength	18 lbs/in (31.52 N/cm)
Elongation (% at Break)	600%
Operating Temperature	-40°F to 190°F (-40°C to 88°C)
Application Temperature	50°F to 120°F (10°C to 49°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.