



Product Information

CT #772

Outdoor Sealing Polyethylene Film Tape

772 is a white polyethylene film with a polyurethane adhesive for outdoor sealing and preservation.

Application:

- High adhesion, high elongation, thick tape for long term outdoor sealing and preservation
- Removes cleanly with no residue

TECHNICAL DATA

Adhesive	Polyurethane
Substrate	White Polyethylene Film
Thickness	10.5 Mils (0.267 mm)
Adhesion to Steel	65 oz/in (7.11N/cm)
Tensile Strength	18 lbs/in (31.52 N/cm)
Elongation (% at Break)	650%
Operating Temperature	-40°F to 190°F (-40°C to 88°C)
Application Temperature	50°F to 120°F (10°C to 49°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.