



Product Information

CT #789

Interior Grade Aromatic Polyurethane Film Tape

789 is an interior grade, repositionable film tape with a thermoplastic aromatic polyurethane adhesive and 92 pound polycoated release liner (transparent).

Application:

- Heavy duty repositionable tape to protect surface in high and low temperatures
- Prevents scratching and chipping due to constant abrasion
- Used in long and short term for shot peening in metal cleaning, automotive, marine, and OEM surface protection applications for vibration and sound dampening for air foil and ground effects panels in motorsports

TECHNICAL DATA

Adhesive	Thermoplastic Aromatic Polyurethane
Substrate	92 lb Polycoated Release Liner
Thickness	9.4 Mils (0.239 mm)
Adhesion to Steel	45 oz/in (4.92 N/cm)
Tensile Strength	70 lbs/in (122.59 N/cm)
Elongation	600% (% at Break)
Operating Temperature	-45°F to 250°F (-43°C to 121°C)
Application Temperature	50°F to 120°F (10°C to 49°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.