



Product Information

CT 822

Single-Coated UV Resistant PVC Foam Tape

Description:

3/16" thick, UV resistant, 8# density, single-coated, closed cell PVC foam tape with an acrylic adhesive that offers long service life. Available in different thicknesses.

Application:

- Gasketing, weather stripping, sound deadening and shock absorption
- Seals out air, moisture, light and dust when compressed at least 30%
- Offers long service life

Technical Data

Adhesive	Acrylic
Substrate	Closed Cell PVC
Thickness	3/16"
Tensile Strength (lbs/in of width)	30 (53.7 N/10mm)
Elongation (% at Break)	150
Application Temperature	50°F to 110°F (10°C to 45°C)
Service Temperature	-40°F to 180°F (-40°C to 82°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.