



Product Information

CT 840 Closed Cell Single-Coated PVC Foam Tape

Description:

3/8" thick, 10 pound density, closed cell PVC foam tape with an acrylic adhesive, paper release liner, and near 100% recovery after extended compression. Also available in 5/16" thick (#863) and 1/4" thick (#864).

Application:

- Designed to meet the extreme demands of the log home industry.
- Makes permanent air and weather-tight seals while eliminating concern over "log float" during construction.
- Excellent resiliency with near 100% recovery after extended compression.

Technical Data

<i>Adhesive</i>	Acrylic
<i>Substrate</i>	PVC Foam
<i>Thickness (mils)</i>	375 Mils (9.525 mm)
<i>Tensile Strength (lbs/in of width)</i>	30 lbs/in (207 kPa)
<i>Elongation (% at Break)</i>	130
<i>Service Temperature</i>	-30°F to 200°F (-35°C to 90°C)
<i>Application Temperature</i>	50°F to 110°F (10°C to 45°C)

Carolina Tape & Supply Corporation
502 19th St. Pl. SE, Hickory, NC 28602
Phone: 800-237-6079
Fax: 828-322-7268
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.