



Product Information

CT #847

High-Density Black Urethane Foam Tape

847 is a 1/32" thick, high-density, closed cell black urethane foam with adhesive coated on one side and an aggressive acrylic adhesive and low density polyethylene film release liner. It is also available in 1/16" thick (#848) and 1/8" thick (#849).

Application:

- Heavy coating weight makes tape excellent for mounting items such as commercial soap dispensers, reflectors, interior/exterior metal and plastic trim, mirror tiles, wire harness clips, nameplates, and for sealing gasketing, and to absorb shock and vibration
- Bond strength increases with aging
- Tape weathers well, resists solvents and chemicals and performs over a wide range of humidity and temperature conditions

TECHNICAL DATA

Adhesive	Acrylic
Substrate	Closed-Cell Black Urethane Foam
Thickness	30 Mils (0.762 mm)
Adhesion to Steel	80 oz/in
Tensile Strength	350 lbs/in
Elongation (% at Break)	290

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.