



## Product Information

### CT #857

### SCE 42 Neoprene/EPDM/SBR Tape

857 is a 1/16" thick SCE 42 Neoprene/EPDM/SBR tape with a black closed cell backing (5 to 7 pound density) and high-tack, rubber-based pressure sensitive adhesive on one side with easy-to-use release liner. It is also available in 1/8" thick (#854), 3/16" thick (#855), and 1/4" thick (#856).

#### Application:

- Conformable, compressible, and highly flexible product for cushioning, sound, and vibration dampening, gasketing, weather stripping, dust proofing, shock absorption, and sealing

#### TECHNICAL DATA

<b>Adhesive</b>	Rubber-Based
<b>Substrate</b>	Black Closed Cell Neoprene/EPDM/SBR
<b>Thickness</b>	60 Mils (1.524 mm)
<b>Adhesion to Steel</b>	128 oz/in
<b>Tensile Strength</b>	100 lbs/in (689.5 kPa)
<b>Elongation</b> (% at Break)	150
<b>Functional Temperature</b>	0°F to 140°F (-17.8°C to 60°C)
<b>Application Temperature</b>	50°F to 80°F (10°C to 26.7°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation  
502 19<sup>th</sup> St PL SE, Hickory, NC 28602  
Phone: 800-237-6079  
[www.carolinatape.com](http://www.carolinatape.com)

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.