

TECHNICAL DATA

Adhesive **Rubber-Based** SCE 41 Substrate Neoprene/EPDM/ SBR Thickness 125 Mils (3.175 mm) Tensile 75 lbs/in Strength Elongation 150 (% at Break) Service -40°F to 250°F **Temperature** (-40°C to 121.1°C)

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

CT #875

SCE 41 Neoprene/EPDM/SBR Closed Cell Foam Tape

875 is a 1/8" thick SCE 41,

neoprene/EPDM/SBR black closed cell foam tape (6 to 11 pound density) with a high tack rubber-based adhesive on one side with easy-to-use release liner. It is also available in 3/16" thick (#876), 1/4" thick (#877), and 5/16" thick (#878).

Application:

- Meets most standard specs for closed cell stock
- Used for cushioning, sound, and vibration dampening, gasketing, insulation, shock absorption, dust proofing, sealing, and weather stripping

Carolina Tape & Supply Corporation 502 19th St PL SE, Hickory, NC 28602 Phone: 800-237-6079 www.carolinatape.com Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.