



Product Information

CT #956

Dead Soft Aluminum Foil Tape

956 is a 2 mil, dead soft aluminum foil with a conductive, acrylic adhesive and a 60 pound release liner.

Meets Specs: UL 510, Section 4 for Flammability.

Application:

- Specifically designed for EMI/RFI shielding and cable wrap applications
- Excellent conformability to irregular surfaces
- Adhesive is uniformly dispersed with conductive spheres to provide very high EMI/RFI shielding

TECHNICAL DATA

Adhesive	Conductive Acrylic
Substrate	Dead Soft Aluminum Foil
Thickness	2.76 Mils (0.07 mm)
Adhesion to Steel	24.7 oz/in
Tensile Strength	16 lbs/in
Elongation (% at Break)	5

The data provided are nominal values based on PSTC, ASTM, and other standard tests. The data should not be considered specifications.

Carolina Tape & Supply Corporation
502 19th St PL SE, Hickory, NC 28602
Phone: 800-237-6079
www.carolinatape.com

Carolina Tape and Supply Corporation guarantees its products to be in compliance with acceptable commercial standards for material and workmanship, but limits its obligations under this warranty to replacement, or, at its option, reimbursement of the purchase price of returned merchandise shown to its satisfaction to have been defective by such standards at the time it was shipped by Carolina Tape and Supply Corporation.